

## SKIDSTEER TRACKED LOADER





## SPECIFICATIONS

### SKIDSTEER TRACKED LOADER COMPLETE WITH:

#### OPERATING SPECIFICATION:

Operating Weight: 5,790kg  
Rated Operating Capacity (35%): 1,975kg  
Rated Operating Capacity (50%): 2,820kg  
Tipping Load: 5,635kg  
Ground Clearance: 245mm  
Ground Pressure (400mm Tracks): 40.5kPa  
Travel Speed: 8.9kph Low / 13.3kph High  
Overall Width: 1,931mm (400mm Tracks)  
Height to Top of Cab: 2,125mm  
Length with Bucket: 3,931mm

#### ENGINE:

CAT C3.8DIT Turbo Diesel Engine  
3.8L, 4-Cylinder Turbo Diesel  
Gross Power: 82kW (110HP)  
Net Power: 79kW (106HP)  
Peak Torque: 374Nm @1500rpm

#### HYDRAULIC SYSTEM:

XE High Flow Hydraulics  
Maximum Hydraulic Pressure: 28,000kPa  
Maximum Hydraulic Flow: 150L/min  
Hydraulic Power (Calculated): 70kW (94HP)  
Standard Flow: 86L/min

#### POWER TRAIN:

Hydrostatic Transmission  
Two Speed Travel  
Electronic Torque Management System  
Independent Torsion Axle Suspension  
Speed Sensitive Ride Control

#### UNDERCARRIAGE AND GUARDS:

Heavy Duty Steel Embed Rubber Tracks, 400mm  
Triple Flange Front and Rear Idlers  
Additional Machine Guarding and Sealing  
Drive-line Guarding and Turbo Guard  
Debris Guarding (External and Turbo)

#### OPERATOR ENVIRONMENT:

ROPS/ FOPS Enclosed Air- Conditioned Cabin  
High Back Heated Air Suspension Seat  
Advanced Display with Rearview Camera  
Adjustable Seat Mounted Joystick Controls  
Polycarbonate Door and Side Windows  
Electronic Hand and Foot Controls

#### SERVICE CAPACITIES:

Fuel Tank: 220L  
Hydraulic System: 55L  
Hydraulic Tank: 39L Engine Crankcase: 13L  
DEF Tank: 19L  
Cooling System: 16L

#### ELECTRICAL SYSTEM:

12V Electrical System  
100 Amp Alternator  
Heavy Duty 1,000 CCA Battery  
LED Front and Rear Work Lights  
Beacon Provision and Backup Alarm